

Far-Field RAIN RFID Antenna



865-868 MHz



The Far-Field panel antennas by Laird are circularly polarized providing reception and transmission of signals in the 865-868 MHz frequency band. Laird's industry renowned design methodology achieves maximum efficiency and performance across the entire frequency band.

Both VSWR and axial ratios are excellent and allow the user to achieve the maximum performance for an antenna of this type. The antennas are housed in a heavy-duty radome enclosure that can be directly wall mounted. An optional articulating mount allows either wall or mast mounting. The antennas are offered with an integrated coax pigtail.

FEATURES AND BENEFITS

- Low profile
- Extremely low VSWR and axial ratio
- Weather and UV-resistant radome
- Left-hand and right-hand CP versions

ELECTRICAL SPECIFICATIONS

Impinj Part Numbers	IPJ-A1000-EU1/IPJ-A1001-EU1
Laird Part Numbers	S8658PLJ96RTN/S8658PRJ96RTN
Operating Frequency (MHz)	865-868 MHz
VSWR – Max	1.5:1
Gain (dBic)	8.5
Nominal Impedance (Ohms)	50
Max Power - Ambient 25°C (W)	10
Polarization	Circular right-hand or circular left-hand
Horizontal Plane 3 dB Beamwidth	70°
Front-to-Back Ratio (dB)	16
Axial Ratio (dB)	2

MECHANICAL SPECIFICATIONS

Dimensions – length x width x height – mm (inches)	259 x 259 x 34 (10.2 x 10.2 x 1.32)
Weight – kg (lbs.)	0.91 (2.0)
Radome Material	High strength PC
Mount Style	Threaded stud
Lightning Protection	DC grounded

ENVIRONMENTAL SPECIFICATIONS


Operating Temperature – °C (°F)	-25 to +70°C (-13 to +158°F)
Environmental Rating	IP 54
Material Substance Compliance	RoHS compliant

CONFIGURATION

IMPINJ PART NUMBERS	LAIRD PART NUMBERS	CONNECTOR
IPJ-A1000-EU1	S8658PLJ-IP1	Coax Pigtail, Rev TNC Male
IPJ-A1001-EU1	S8658PRJ-IP1	Coax Pigtail, Rev TNC Male

RADIATION PATTERN

867 MHz



Laird warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations Laird will, at its option, either repair or replace any part of its products that prove defective because of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the Laird product is installed. Useful lifetime of the original end product may vary but is not to exceed five (5) years from the original date of the end product purchase.

Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird shall not be liable for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request.

© Copyright 2018 Laird Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trademarks or registered trademarks of Laird Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.

Impinj is a registered trademark of Impinj, Inc.

